| Generate Collection | Print |
|---------------------|-------|
|                     | L     |

| Search Results - Record(s) 1 through 7 of 7 returned.  |  |  |
|--|--|--|
| ] 1. <u>1208495</u> .; 12 Dec 16. TEXT NOT AVAILABLE. Name not available. 49/184; 49/173.  |  |  |
| 2. JP 2002541593 W WO 200062224 A1 AU 200042069 A EP 1208495 A1. Process for determining object level profitability in relational database management system, involves calculating and combining marginal value of profit and fully absorbed profit adjustment value for each object. LEPMAN, R T. G06F017/30 G06F017/60.  |  |  |
| 3. <u>US 5651038 A KR 99082245 A WO 9729489 A1 AU 9713842 A ZA 9700076 A EP 879467 A1 CN 1208495 A JP 2000504827 W</u> . Sealed basket for pressurised water reactor fuel assemblies - comprises internal assembly with independent sleeves, cylindrical shell, internal support structure and neutron poison sheet, for transport and storage. CHECHELNITSKY, B A, et al. G21C019/32 G21F000/00 G21F005/002 G21F005/005 G21F005/008 G21F005/012 G21F009/36. |  |  |
| 4. <u>EP 287006 A</u> . Fertiliser spreader with funnel-shaped hoppers - has clutch between each stirring mechanism and central gearbox. WEISTE, H. A01C017/00.  |  |  |
| 5. <u>SU 1208495 A</u> . Determn. of binder content in woodried sample in air with specified relative humidity and using content. MELNIKOV, S F. G01N005/02.   | od moulding material - involves holding g moisture absorption to assess binder |  |
| ☐ 6. DE 3502522 A AT 8500245 A AT 8602142 A CH 662710 A FR 2559358 A FR 2564326 A IT 1208495 B US 4698920 A US 4788781 A US 4790081 A US 4951402 A. Ski boot operating lever - is U=shaped with ends joined to axle on back. BENOIIT, L, et al. A42B000/00 A43B005/04 A43C003/04 A43C011/14 A63C011/16.  |  |  |
| 7. EP 102334 A AU 8317532 A BR 8304117 A CA 1208495 A DE 3377734 G DK 8303535 A EP 102334 B ES 8406629 A FI 8302727 A KR 8901725 B NO 8302795 A US 4472107 A. Rotary fluid handling machine - has balancing chamber defined by stationary housing and rotor, to offset net axial thrust loads on rotor shaft. CHANG, C M, et al. F01C007/00 F01C019/00 F01D003/02 F01D011/02 F04D001/00 F04D029/00.  |  |  |
| Generate Collection Print  |  |  |
| Terms  | Documents  |  |
| 1208495  | 7  |  |
|  |  |  |

Previous Page

Next Page